

WHEN SAFETY COMES FIRST  
**SPRAYDRENCH**<sup>®</sup>  
 EMERGENCY SAFETY SHOWERS

MO 011 SHPC



Detailed Description

Manually Push Plate Operated Single Column Shower c/w Centrally Mounted Hand Operated Rigid Eyewash Station c/w Twin Aerator Nozzle with Dust Caps

Optional Extras

- Scald &/or Freeze Protection Valve
- Shower Support
- Additional Options Available on Request

Best Suited Applications

- Moderate risk areas
- Battery charging areas
- Dipping operations
- Sample points
- Mining general processing
- Laboratories
- Fuel load/offloading

Inlet : 1" BSP(F)

Primary Shower Nozzle (1 off SD10DN)

Secondary Shower Nozzle (1 off SD12DN)

Eyewash: Twin Aerator Nozzles

Flow Rates at design pressure of  $\pm 2.5$  bar(g)



MO 011 SHPC

Additional Info.

Material of Construction Stainless Steel  
 Approx. Floor Foot Print (cm)  $\pm 120$  (L) x 800 (W) x 243 (H)  
 Single Unit Weight (kg)  $\pm 16$   
 Typ. Single Unit Pack Dim. (cm)  $\pm 157$  (L) x 74 (W) x 34 (H)

All **SPRAYDRENCH**<sup>®</sup> products are manufactured according to the following standards:

ANSI Z358.1-2014  
 DIN 12899-3:2008

EN15154-1:2006-12  
 EN15154-2:2006-12  
 EN15154-5:2019-12

Further Detail Available on Request

TEL: +27 (0)11 466 2100 | FAX: +27 (0)11 466 0618

**spray nozzle** (PTY) LTD

sales@spraynozzle.co.za

PO BOX 2369, HALFWAY HOUSE, SOUTH AFRICA, 1685 | REG:1971/014137  
 WWW.SPRAYDRENCH.CO.ZA | WWW.SPRAYNOZZLE.CO.ZA

