

WHEN SAFETY COMES FIRST  
**SPRAYDRENCH**<sup>®</sup>  
 EMERGENCY SAFETY SHOWERS

MO 011 EHO



Detailed Description

Epoxy-Coated Mild Steel Manually Overhead Pull Operated Single Column Shower c/w Hand/Push Operated Rigid Emergency Eyewash Station c/w Twin Aerator Nozzle with Dust Caps

Optional Extras

- Scald &/or Freeze Protection Valve
- Shower Support
- Additional Options Available on Request

Best Suited Applications

- Moderate risk areas
- Battery charging areas
- Low risk chemical storage
- Industrial workshops
- General manufacturing
- Fuel load/offloading

Inlet : 1" BSP(F)

Primary Shower Nozzle (1 off SD10DN-PP)  
 85 lpm

Eyewash: Twin Aerator Nozzles  
 20 lpm

Flow Rates at design pressure of ±2.5 bar(g)

Additional Info.

Material of Construction Epoxy Coated Carbon Steel  
 Approx. Floor Foot Print (cm) ±120 (L) x80 (W) x250 (H)  
 Single Unit Weight (kg) ±16  
 Typ. Single Unit Pack Dim. (cm) ±157 (L) x74 (W) x34 (H)

All **SPRAYDRENCH**<sup>®</sup> products are manufactured according to the following standards:

ANSI Z358.1-2014  
 DIN 12899-3:2008

EN15154-1:2006-12  
 EN15154-2:2006-12  
 EN15154-5:2019-12

Further Detail Available on Request

Manually Operated

Single Column Free Standing

Epoxy Coated Carbon Steel

Hand Operated Eye Wash

Shower Overhead Pull Operated

MO 011 EHO

TEL: +27 (0)11 466 2100 | FAX: +27 (0)11 466 0618

**spray nozzle** (PTY) LTD

sales@spraynozzle.co.za

PO BOX 2369, HALFWAY HOUSE, SOUTH AFRICA, 1685 | REG:1971/014137  
 WWW.SPRAYDRENCH.CO.ZA | WWW.SPRAYNOZZLE.CO.ZA

**SPRAYDRENCH**<sup>®</sup>  
 EMERGENCY SAFETY SHOWERS