

WHEN SAFETY COMES FIRST
SPRAYDRENCH[®]
 EMERGENCY SAFETY SHOWERS

MO 011 SHP



Detailed Description

Manually Push Plate Operated Single Column Shower c/w Hand/Push Operated Rigid Emergency Eyewash Station c/w Twin Aerator Nozzle with Dust Caps

Optional Extras

- Scald &/or Freeze Protection Valve
- Shower Support
- Additional Options Available on Request

Best Suited Applications

- Moderate risk areas
- Battery charging areas
- Dipping operations
- Sample points
- Mining general processing
- Laboratories
- Fuel load/offloading

Inlet : 1" BSP(F)

Primary Shower Nozzle (1 off SD10DN-PP)

85 lpm

Secondary Shower Nozzle (1 off SD12DN BR)

31 lpm

Eyewash: Twin Aerator Nozzles

20 lpm

Flow Rates at design pressure of ±2.5 bar(g)

- Manually Operated
- Single Column Free Standing
- Stainless Steel
- Hand Operated Eye Wash
- Shower Push Plate Operated

MO 011 SHP

Additional Info.

Material of Construction Stainless Steel
 Approx. Floor Foot Print (cm) ±120 (L) x800 (W) x243 (H)
 Single Unit Weight (kg) ±13
 Typ. Single Unit Pack Dim. (cm) ±157 (L) x74 (W) x34 (H)

All **SPRAYDRENCH**[®] products are manufactured according to the following standards:

ANSI Z358.1-2014
 DIN 12899-3:2008

EN15154-1:2006-12
 EN15154-2:2006-12
 EN15154-5:2019-12

Further Detail Available on Request

TEL: +27 (0)11 466 2100 | FAX: +27 (0)11 466 0618

spray nozzle (PTY) LTD

sales@spraynozzle.co.za

50 SILVERSTONE CRES, KYALAMI BUSINESS PARK, JOHANNESBURG, SOUTH AFRICA 1684
 PO BOX 2369, HALFWAY HOUSE, SOUTH AFRICA, 1685 | REG:1971/014137
 WWW.SPRAYDRENCH.CO.ZA | WWW.SPRAYNOZZLE.CO.ZA

